

PPC-GS1073T

Pictures



Features:

- Intel ® Core 6th i3 CPU
- 9.7" TFT LED screen
- Resistive touch screen
- Fully-sealed fanless design, suitable for harsh industrial environment applications
- 2GB DDRIII, 8GB optional
- SSD or HDD
- 4*USB 3.0
- 4*RS232(1-2*RS422/RS485 optional)
- 1*VGA/1*HDMI
- 2* intel i211 GbE
- 9-24 V wide-range DC Input
- Color: Silver/Black/White

Specifications:

Display Feature	Display Screen	9.7" TFT LED
	size ratio	4:3
	Resolution	1024*768
	Brightness	350 cd/m2
	Contrast ratio	900:1
	Touch Screen	Resistive touch screen
Performance	Chipset	Intel ® Core 6 th i3 CPU
	Memory	2G DDR3, 8GB optional
	Hardware Monitor	Monitors voltage, Temperature
	Watchdog Timer	0 to 255 sec by software
	Storage	SSD or HDD
Power	Power Supply	100~240VAC/50~60Hz(Power adapter) 9-24V DC (No power adapter)
O/S	Operating System	Windows 7/ Windows 8/ Linux
I/O Interface	USB	4 *USB3.0 Ports
	Serial Port	4*RS232 (1-2*RS422/RS485 Optional)
	Ethernet	2* intel i211 GbE RJ45
	Audio	1*Line out, 1*Mic in
	Display	1* VGA, 1*HDMI
	GPIO	4 in/out optional
	Expansion	1*Mini PCIe
Environmental	Anti-vibration	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g,acceleration
	Anti-shock	10g acceleration, 11ms duration
	IP Level	Front panel IP65 (Optional)
	Reliability	MTBF≥50000h; MTTR≤0.5h
	Operating Temperature	-20℃～60℃ (with air flow)
	Storage Temperature	-30℃ ～70℃
	Operating Humidity	95% @40℃, non-condensing
Mechanical	Dimensions	258mm (L) *198 mm (W) *58.5 mm (H)
	Material	Fanless High-strength and elegant Al-alloy panel
	Weight	2.5kg/4.0kg (NET./GROSS.)
	Color	Silver/Black/White