

PPC-GS1092T

Photos:



Feature:

- Chipset: Rk3288 SoC Cortex-A17 quad core @ 1.8Ghz Max
- 10.1" Touch Screen
- Multi-touch Capacity Touch Screen
- 2GB RAM on board, 8G NANDFLASH storage
- 2*USB2.0/4*RS232/1*HDMI
- 1* 1000M LAN
- Fanless Industrial Design
- Color: Black or optional

Specification:

Display Feature	Display Screen	10.1" TFT LED
	Touch Screen	Multi-touch Capacitive touch screen
	Contrast ratio	800:1
	Resolution	1280*800
	Brightness	400 cd/m2
Performance	Chipset	Rk3288 SoC Cortex-A17 quad core 1.8Ghz Max
	Memory	On board 2GB RAM
	Hardware Monitor	Monitors voltage, TEMP and CPU fan speed
	Storage	On board 8G NAND FLASH
Power	Power Supply	100~240VAC/50~60Hz (With power adapter) 12VDC/5A (Without Power adapter)
	Power Dissipation	8W
OS	OS	Andriod 5.1
I/O Ports	USB	2*USB2.0
	Serial Ports	4*RS232
	LAN	1*1000M
	Audio	Line out
	Display	1*HDMI
	Blue tooth	4.0
Expension	WIFI	support
	GPS	Optional
	3G	Optional
	RFID	Optional
Environmental	Anti-vibration	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g, acceleration
	Anti-shock	10g acceleration, 11ms duration
	IP Level	IP65 (Optional)
	Reliability	MTBF $\geq$ 50000h; MTTR $\leq$ 0.5h
	Operating Temperature	-20℃ $\sim$ 60℃ (with air flow)
	Storage Temperature	-30℃ $\sim$ 70℃
	Operating Humidity	95% @40℃, non-condensing
Mechanical	Dimensions	268mm (L) *195mm(W) *37.4mm (H)
	Material	Fanless High-strength and elegant AL-alloy pane
	Weight	1.5kg/2.0kg(N/G)
	Color	Black or optional