

PPC-GS1573HT

Pictures



Features:

- Intel ® Core i3 (i5/ i7 optional)
- 15" TFT LED screen
- Capacitive touch screen
- Fully-sealed fanless design, suitable for harsh industrial environment applications
- 2G memory (DDR3) on board, Max 8GB optional
- 4* USB 3.0+ 1* USB in front panel
- 4* RS232 (1-2* RS422/RS485 optional)
- 9-36V wide-range DC Input
- One-year warranty
- Color: Silver

Specifications:

Display Feature	Display Screen	15" TFT LED
	size ratio	4:3
	Resolution	1024x768
	Brightness	300 cd/m2
	Contrast ratio	400:1
	Touch Screen	Full size 5-wire Resistive Touchscreen (Capacitive Touchscreen Optional)
Performance	Chipset	Intel® Core i3 (i5 i7 optional)
	Memory	2G memory (DDRIII)on board , 4GB/8GB optional
	Hardware Monitor	Monitors voltage, Temperature
	Watchdog Timer	0 to 255 sec by software
	Storage	64GB/1* mSATAIII, 1*SATAIII 2.5 inch
Power	Power Supply	9-36V DC
I/O Interface	USB	5*USB3.0 (1*USB on Front Panel)
	Serial Port	4*RS232, Optional 1-2RS485/RS422
	Ethernet	2*Intel 10/100/1000M RJ45
	Audio	1*Mic&Line-out 2in1
	Display	1*HDMI1.4, 1*VGA
	GPIO	N/A
	Expansion	1*Mini PCIe
O/S	O/S	Windows 7/ 8/ 10,Linux
Environmental	Anti-vibration	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g, acceleration
	Anti-shock	10g acceleration, 11ms duration
	IP Level	Front panel IP65 (Optional)
	Reliability	MTBF≥50000h; MTTR≤0.5h
	Operating Temperature	-0℃～50℃ with HDD (-20℃～70℃ with SSD) with air-flow
	Storage Temperature	--40℃ ～80℃
	Operating Humidity	95% @40℃, non-condensing
Mechanical	Dimensions	500*440*190mm
	Material	High-strength and elegant Al-alloy panel
	Weight	5.2kg/6.8kg (NET./GROSS.)
	Color	Silver